



LP-WU6600

1-Chip DLP laser projector, 6000 ANSI Lumens, 20000:1 contrast ratio, WUXGA (1920 x 1200) resolution

HITACHI
Inspire the Next

Technical Specifications



- a:** Projection distance
- b:** Lens centre to the higher edge of the screen
- c:** Lens centre to the lower edge of the screen

IMAGE SIZE 16:10 (FROM PROJECTOR'S LENS END)

Screen size (diagonal)	HxV		Projection distance (a)		Screen height (cm)	
	m	m	Wide (m)	Tele (m)	b (top)	c (bottom)
36" (0.9 m)	0.8	0.5	1.2	1.5	51	2
50" (1.3 m)	1.1	0.7	1.7	2.1	71	-3
100" (2.5 m)	2.2	1.3	3.3	4.2	141	-7
150" (3.8 m)	3.2	2.0	5.0	6.2	212	-10
211" (5.3 m)	4.5	2.8	7.0	8.8	298	-14

IMAGE SIZE 16:9 (FROM PROJECTOR'S LENS END)

Screen size (diagonal)	HxV		Projection distance (a)		Screen height (cm)	
	m	m	Wide (m)	Tele (m)	b (top)	c (bottom)
36" (0.9 m)	0.8	0.4	1.2	1.6	50	-5
50" (1.3 m)	1.1	0.6	1.7	2.1	69	-7
100" (2.5 m)	2.2	1.2	3.4	4.3	138	-14
150" (3.8 m)	3.3	1.9	5.1	6.4	208	-21
211" (5.3 m)	4.7	2.6	7.2	9.0	292	-29

As a result of using standard SD-63 Lens

OPTICAL

Display System	1-chip DLP (0.67 inches)
Resolution	WUXGA (1920 x 1200) 16:10 aspect Ratio
Light Output (Brightness) ANSI Lumens	6000 (Normal), 4670 (Eco)
Contrast Ratio	20,000:1
System Life (Hours)	20,000
Lens	Interchangeable, not included
Lens Zoom	Manual x 1.25 (using SD-63)
Lens Focus	Manual Focus
Lens Shift	Manual
Projection Lens F Number	2.0 – 2.09
Focus Distance	1.5 – 7m (SD-63 Lens)
Distance to Width Ratio / Throw Ratio:1	1.54 (Wide), 1.93 (Tele) (using SD-903 lens)
Display Size Diagonal	36 – 380 inches (using SL-62 Short Throw lens), 36 – 211 inches (using Standard lens SD-63), 32 – 481 inches (using long throw ML-64 lens)

FEATURES

Speakers	12W (mono) or 6W x 2 (mono)
Digital Keystone	Vertical $\pm 30.0^\circ$, Horizontal $\pm 25.0^\circ$
Picture Modes	Presentation / Bright / Game / Movie / Vivid / TV / sRGB / DICOM SIM / User 1 / User 2
Supported Languages	English, French, German, Spanish, Portuguese, Simplified Chinese, Traditional Chinese, Italian, Norwegian, Swedish, Dutch, Russian, Polish, Finnish, Greek, Korean, Hungarian, Czech, Arabic, Turkish, Vietnamese, Japanese, Thai, Farsi, Hebrew, Danish, French Canadian

CONNECTIONS

Digital Input	HDMI x 2, DVI-D x 1, HDBase-T x 1
Analogue Input	15 pin Mini D-Sub x 1, 5BNC x 1
Video Output	15 pin Mini D-Sub x 1
Audio Input	3.5mm Stereo Mini Jack x 1, RCA Jack (L/R) x 1
Audio Output	RCA jack L/R x 1
RS-232C Control	1 x 9-pin D-Sub
Wired LAN	Yes
USB Type-A	Yes
USB Type-B	No
12V Trigger	3.5mm Stereo Mini Jack x 1
Wired Remote Input & Output	3.5mm Stereo Mini Jack x 1 (input) / 3.5mm Stereo Mini Jack x 1 (output)
3D Sync Input & Output	VESA 3-pin x 1 (input) / VESA 3 pin x 1 (output)

POWER

Power Supply	AC 100V – 120V / AC 220V – 240V (50/60Hz)
Power Consumption Operating / Standby	700W / Less than 0.5W

PHYSICAL

Weight	24.5kg
Dimensions (W x H x D)	521 x 220 x 470mm (Excluding lens)
Noise	35db (Normal), 33db (Eco)

ACCESSORIES

Lenses	SL-62 (Short Throw Lens), SD-63 (Standard Lens), ML-64 (Long Throw Lens)
Remote Control	HL03171

WARRANTY

Projector / System Life	10,000 hours / 5 years (whichever comes first) (for extended warranty please contact your local dealer)
-------------------------	---

LENS OPTIONS

Lens Code	Lens Type	Projection Distance For 100 inch Screen (Full Screen) (Projector's Front Panel to Screen)	Throw Ratio
SL-62	Short throw lens, Zoom x 1.18	2.4 – 2.8m	1.1 – 1.3
SD-63	Standard lens, Zoom x 1.25	3.3 – 4.1m	1.54 – 1.93
ML-64	Long throw lens, Zoom x 1.5	4.1 – 6.2m	1.93 – 2.9

